

REV DATE: 2003






LANE MARKER-TYPE 1

DIRECTION OF TRAFFIC








LANE MARKER-TYPE 2B

REF STD SPEC SEC 9-21




NOT TO SCALE

TRAFFIC BUTTONS & LANE MARKERS



REF STD SPEC SEC 8-08






APPROACH LINE LENGTH LESS THAN 50 FEET 50 FEET—120 FEET 125 FEET—300 FEET LEGEND SETS

1 SET AT X-WALK END OF POCKET
2 SETS

OVER 300 FEET

3 SETS (SECOND LEGEND LOCATED MIDWAY BETWEEN FIRST AND LAST LEGENDS) ADDITIONAL SETS SPACED AT APPROX 100 FT INTERVALS BETWEEN FIRST AND LAST SETS



TYPICAL TWO WAY LEFT TURN LANES

NUMBER OF LEGEND SETS REQUIRED BASED ON THE


LENGTH OF TYPICAL TWO WAY LEFT TURN LANES

LANE LENGTH LESS THAN 50 FEET 0 FEET-300 FEET OVER 300 FEET LEGEND SETS


1 SET (CENTERED BETWEEEN BOTH ENDS OF LANE)
2 SETS

2 SETS


ADDITIONAL SETS SPACED AT APPROX 300 FT INTERVALS



LEGEND PLACEMENT LEGENDS IN ADJACENT LANES SHALL BE ALIGNED AS SHOWN



LEGENDS SHALL BE CENTERED WITHIN THE LANE TO WHICH THEY APPLY, AS SHOWN



LEGEND COMBINATIONS

OBLIQUE LEFT & 90° LEFT LEGENDS AND
OBLIQUE RIGHT & 90° RIGHT LEGENDS
MAY BE COMBINED AS SHOWN


REF STD SPEC SEC 8-22




NOT TO SCALE

TYPICAL LEFT TURN
CHANNELIZATION AND LEGEND
PLACEMENT

REV DATE: 2003





TYPICAL LADDER PEDESTRIAN CROSSWALKS

* WHERE TRAFFIC LANE LINES ARE NOT USED, LADDER BARS SHALL BE 5'-0" CENTER TO CENTER, BEGINNING AT THE MARKED CENTERLINE OF THE ROADWAY

NOTES:

- EXACT LOCATION OF CROSSWALK LINES AND STOP LINES
 SHALL BE DESIGNATED BY SEATTLE DEPARTMENT OF
 TRANSPORTATION
- 2. EXISTING CROSSWALKS IN CONFLICT WITH NEW OR REVISED CROSSWALKS SHALL BE REMOVED BY MACHINE GRINDING


REF STD SPEC SEC 8-22





TYPICAL CROSSWALK & STOP
LINE INSTALLATION DETAILS


REV DATE: 2003 L - 10PASSENGER LOAD ZONE, ETC (WHITE) L - 11TOW-AWAY ZONE (RED) L - 12COMMERCIAL LOAD, TRUCK LOAD, LOAD & UNLOAD ZONE, ETC (YELLOW) 3'-0" 4'-0" 3'-0" VARIABLE 3'-0" 4'-0" 3'-0" RED YELLOW RED (10'-0" MAX) RED YELLOW RED L - 13BUS ZONE (NON PARKING METERED AREAS) BUS ZONES ARE PAINTED ON TOP & FACE OF CURB TOP OF CURB FACE OF CURB 3'-0" 4'-0" 3'-0" 4'-0" 3'-0" 4'-0" YELLOW RED YELLOW RED YELLOW RED YELLOW RED YELLOW BUS ZONE (PARKING METERED AREAS) BUS ZONES ARE PAINTED ON TOP & FACE OF CURB NOTES: 1. TOTAL LENGTH OF CURB MARKINGS SHALL BE AS SHOWN ON DRAWINGS 2. PAINT SHALL BE APPLIED NEATLY ON THE CURB AND ALL PAINT SMEARS ON ADJACENT SURFACES SHALL BE REMOVED **REF STD SPEC SEC 8-22 CURB SPACE** City of Seattle NOT TO SCALE MARKING DETAILS

STANDARD PLAN NO 720a










REF STD SPEC SEC 8-22



NOT TO SCALE


PAVEMENT MARKINGS LEGENDS/SYMBOLS


STANDARD PLAN NO 720b





STANDARD PLAN NO 721

REV DATE: 2005









NOTE: "T" = THERMOPLASTIC


REF STD SPEC SEC 8-22




NOT TO SCALE

PAVEMENT MARKINGS LEGENDS/SYMBOLS

STANDARD PLAN NO 722




DATE: 2005





B= BASE WIDTH (12" OR 24" TYPICALLY) H= HEIGHT (18" OR 36" TYPICALLY)

L-9A, L-9AT YIELD LINE



L-28B, L-28BT DENVER ARROW



NOT TO SCALE

PAVEMENT MARKINGS LEGENDS / SYMBOLS